



## Eco Rack Unit

Eco Rack unit is developed to deliver optimal water quality by ultrafiltration.

The unit is delivered preassembled with pipes, fittings and taps. 3 size options available. The only plumbing needed is to connect the unit to the inlet and outlet. Supplied flexi hoses with 3/4" female pipe threads makes the job easy for the plumber. The unit has a convenient drip tray at the bottom to avoid spills when changing filters. The unit is delivered with two prefilters (5 and 1 micron), followed by the unique Eco Solution water filter technology to ensure safe and pure water at all times, also from outbreaks of bacteria and/or parasites from the water line. All components are manufactured by renowned international manufacturers and the purification specifications are well documented. The system is operated solely by water pressure.

The purification system removes:

- 99,99% of pathogenic bacteria (E.g. E.Coli, Salmonella, Legionella, Cholera, Shigella, Typhoid)
- 99,999 % of parasites (E.g. Cryptosporidium, Giardia)
- 97 % chlorine
- 99,7 % turbidity
- Bad smell, color and taste
- Particles, humus and other sediments
- The unit also reduces the levels of some dangerous chemicals and heavy metals



Add on: Eco Dispence dosing system for Desinaqua disinfection fluid can be added in cases where bacterias like legionella might occur in the water lines after the purification system; like at dental offices where backflush can happen.



## Specifications

1.500 - 4.500 liter pr. hour at 4 bars pressure. Filter change recommended every 12 months (daily use). The unit is to be installed on the water intake.

Small; H:97 W:40 D:20  
Medium; H:141 W:40 D:20  
Large; H:178 W:40 D:20



[www.ecowater.no](http://www.ecowater.no)